

## Product Information & Installation Guide

### Bike Hoop Surface Mount Galvanised



**SKU:** BHOOPGALSM

**Description:** Galvanised surface mount hoop bike rack

**Material:** Hot dipped galvanised steel

**Height:** 910mm

**Weight:** 15.00 KGS

**Width:** 800mm

*12 Month Manufacturer's Warranty*


### Installation Guide

#### You will need:

- A hammer drill with a 14mm masonry drill bit
- The M10 screw fixings supplied with the bike hoop.
- A 17mm socket
- A hammer
- A hand broom or industrial vacuum (optional)

#### What to do:

1. Read all the instructions from beginning to end first.
2. Determine exactly where the bike hoop will be placed. If you are installing more than one bike hoop, it is a good idea to mark the ground to ensure that you have a straight line to assist you with the correct placement of your bike hoops.
3. Using your hammer drill, drill a guide hole in the concrete through each hole in the bike hoops using the 14mm masonry drill bit. (This is to mark the surface so that you know where to continue to drill).
4. Remove the bike hoop and brush or vacuum away the concrete dust.
5. Continue to drill each guide hole to an approximate depth of 120mm.
6. Brush or vacuum away the concrete dust.
7. Put the plastic plug component of the fixing in the drilled hole and hammer in.
8. Place each bike hoop over the holes, line up and put the supplied M10 screws through the bike hoop and into the plastic plugs.
9. Use your 17mm socket to tighten the M10 screws. Be careful not to overtighten the screws.



For a seamless installation, ensure your bike hoop is placed on a flat surface.

*Safety Xpress recommends you put the safety of yourself and others first when installing your bike hoop.  
Please be mindful of using and wearing the correct safety gear.*