

SAFE & Installations

INSTALLATION

BOLLARD- TWIST SURFACE MOUNT REMOVABLE

YOU WILL NEED:

- A hammer drill with the correct size drill bit
- The fixings for the bollard
- The correct sized socket
- A hammer
- A hand broom or industrial vacuum (optional)

WHAT TO DO:

- 1. Read all the instructions from beginning to end first.
- 2. Determine exactly where the bollard will be placed. Place the bollard with the base plate receiver attached into the position you would like it to be in when it is in its locked position. Then without moving the position of the base plate, remove the bollard by unlocking the key and turning it anticlockwise from one of the triangle marks to the other. Lift the bollard away from the base plate.
- 3. If you are installing more than one bollard, it is a good idea to mark the ground to ensure that you have a straight line to assist you with the correct placement of your bollards.
- 4. Using your hammer drill, drill a guide hole in the surface, through each hole in the base plate receiver using the drill bit. (This is to mark the surface so that you know where to continue to drill).
- 5. Remove the base plate receiver and brush or vacuum away the dust.
- 6. Continue to drill each guide hole to almost the entire length of your fixings.
- 7. Brush or vacuum away the surface dust.
- 8. Put the plastic plug component of the fixing in the drilled hole and hammer in.
- 9. Place each base plate receiver ove rhte holes, line up and put the supplied fixings through the base plate receiver an into the plastic plugs.
- 10.Use your socket to tighten your bollard onto the base plate receiver, ensure that the key is always turned to the unlock position before being placed onto the base.

Important- When removing the bollard from the base and storing, gently rest the bollard on the ground after removal from the base plate. Do not allow the bollard to hit the ground with force as this will cause irreparable damage to the locking pin. Ideally, hanging (Bollard Storage) is the best storage method for this bollard when not locked into the base plate.



TIP: FOR A SEAMLESS INSTALLATION, ENSURE YOUR BOLLARDS ARE PLACED ON A FLAT SURFACE

Safety Xpress recommends you put the safety of yourself and others first when installing your bollards. Please be mindful of using and wearing the correct safety gear.

WWW.SAFETYXPRESS.COM.AU