

**Portable Eye Wash Station 60L
Users Guide**

Application: Self-contained 16 Gallons gravity flow eyewash unit uses gravity to deliver water through dual spray heads. Unit delivers over 7 Gallons(26 liters) of water for fifteen minutes. Unit is ideal for use where a continuous supply of potable water is not available, especially in remote plant areas, low traffic and/or low hazard areas.

TANK: 16 gallon capacity safety yellow polyethylene tank. Tank has handles on top and side to allow for easy handling. A wide-fill opening with threaded cap permits easy inspection, cleaning and filling.

Mounting :Stainless steel bracket for mounting unit on wall. °
Unit can also be placed on countertop or other flat surface

Preparation: Top operate unit, fill unit with clean potable water and add bacteriostatic additive. Additive protects against growth of bacteria, fungus, algae and acanthamoeba. Unit should be inspected regularly and water in unit should be changed at least once every six months.

Operation: Water flow is activated by pulling down green e wash tray. This action will automatically activate the water spr Lower head until eyes enter eyewash stream, holding eyelids op with thumbs and forefingers. Allow water to flush eyes for minimum of 15 minutes After flushing, seek qualified medi attention immediately.

Drain: Waste water is directed into drain opening in tank basin. 3 ft long drain hose in basin directs discharge into floor drain, storage tank or other receptor.

Discharge time: Eyewash delivers over 1.6L per minute for 15 minutes.

Net Weight: 7.8kg, 68kg full

Quality Assurance: Unit is completely assembled and water tested prior to shipment.

Standard Meet: EN 15154-4:2009, AS 4775-2007, ANSI Z358.1-2014 **Country of Origin:** China

