


FRP Stair Nosing

Industrial fibreglass reinforced plastic stair nosing is hard wearing and suitable for high traffic access stairs and platforms such as marine, mining and factory environments. Due to its extremely hard grit this FRP stair nosing provides an aggressive non slip surface even in wet, oily, greasy or dusty environments. We recommend installation by adhesive to the substrate.




FRP Stair Nosing 70mm x 10mm

SKU: FRP70X10
Material: FRP


Material: FRP
Colour: Yellow or Black

Slip Rating: P5
Width: 70mm
Nose/Face: 10mm




FRP Stair Nosing 70mm x 30mm

SKU: FRP70X30
Material: FRP
Colour: Yellow
Slip Rating: P5
Width: 70mm
Nose/Face: 30mm



FRP Stair Nosing 150mm x 30mm


SKU: FRP150X30
Material: FRP
Colour: Yellow
Slip Rating: P5
Width: 150mm
Nose/Face: 30mm



FRP Stair Nosing 230mm x 30mm

SKU: FRP230X30

Material: FRP
Colour: Yellow
Slip Rating: P5
Width: 230mm
Nose/Face: 30mm



FRP Stair Nosing 230mm x 30mm

SKU: FRP230X30BY

Material: FRP

Colour: Black with yellow nose

Slip Rating: P5 Width: 230mm Nose/Face: 30mm



FRP Anti Slip FRP Decking Strip 50mm

SKU: FLATFRPY
Material: FRP

Colour: Yellow or Black

Slip Rating: P5
Width: 50mm





XMIN181202559CCM

Dec.28, 2018 Date:

Page: 1 of 4

Sample Name FRP ANTI-SLIP STRIP

Material FRP

Spec. 5# EMERY

Above information and sample(s) was/were submitted and confirmed by the client. SGS, however, assumes no responsibility to verify the accuracy, adequacy and completeness of the sample information provided by client.

Test Required Selected test(s) as requested by applicant

Date of Receipt Dec.21, 2018 **Testing Start Date** : Dec.21, 2018 Testing End Date : Dec.27, 2018

Test result(s) For further details, please refer to the following page(s)

(Unless otherwise stated the results shown in this test report refer only to the

sample(s) tested)

******* To be continued*******

Signed for

SGS-CSTC Standards Technical Services Co., Ltd. Xiamen Branch

Testing Center

Civi Huang

Authorized Signatory



No.31 Xianghong Road, Xiang'An Torch Industrial Zone, Xiamen, Fujian Province, China. 36 1101 t (86-592) 5765857 f (86-592) 5765890 www.sgsgroup.com.cn

中国·福建·厦门·火炬 (朔安)产业区朔虹路31号 邮编:361101 t (86-592) 5765857





No.: XMIN181202559CCM

Date: Dec.28, 2018

Page: 2 of 4

Summary of test results:

No.	Test item(s)	Test method(s)	Test result(s)	
1	Wet pendulum test	AS 4586:2013 Amdt 1-2017 Appendix A	SRV "wet": 76 Class: P5	
2	Static coefficient of friction	ASTM C1028-07	Dry condition: 1.25 Wet condition: 1.10	

****** To be continued******







No.: XMIN181202559CCM

Date: Dec.28, 2018

Page: 3 of 4

1. Wet Pendulum Test

Test Method:

AS 4586-2013 Amdt 1-2017 Slip resistance classification of new pedestrian surface materials - Appendix A

- Wet Pendulum Test Method

Rubber slider: slider 96(IRHD 96±2 at 23±3 ℃)

Sample Description:

Plate, 200mm×200mm, 6pcs, see photo(s)

Test Result:

Testing surface: roughness face, see photo(s)

Specimens identification No.	1	2	3	4	5	6
Mean of British Pendulum Number (for each test surface)	74	76	75	76	77	75
Slip resistance value (SRV *wet")	76					
Class	P5					

Classification of pedestrian surface materials according to the wet pendulum test:

Class	Pendulum SRV (slider 96)
P5	>54
P4	45-54
P3	35-44
P2	25-34
P1	12-24
P0	<12

******* To be continued******



|Rec31|| Xianghong Road, Xianghin Torch Industrial Zone, Xianen, Fujan Province, China. 381101 t (86/882) \$765857 f (86/882) \$765850 www.spagnoup.com.cn 中国・豪康・夏行・大臣(海安)产业区無収益31号 施兵稿: 381101 t (86/882) \$765857 f (86/882) \$765860 e sept-china@lega.com





No.: XMIN181202559CCM

Date: Dec.28, 2018

4 of 4 Page:

2. Static coefficient of friction

Test Method:

ASTM C1028-07 Standard Test Method for Determining the Static Coefficient of Friction of Ceramic Tile and Other Like Surfaces by the Horizontal Dynamometer Pull-Meter Method

Sample Description:


Plate, 200mm×200mm, 3pcs, see photo(s)


Test Result:

Testing surface: roughness face, see photo(s)

Static Coefficient of Friction for Dry Surface	1.25
Static Coefficient of Friction for Wet Surface	1.10

Specimen photograph(s):





SGS authenticate the photo(s) on original report only *******End of report*****



| No.31 Xanghong Road, Xang An Torb Industrial Zone, Xamen, Fujan Posinos, China. 361101 1 (86-882) 5765867 f (86-882) 5765860 www.s.gagnoup.com.cn 中国・裏庫・裏门・大阪(海安)产业区無収施31号 無線: 361101 1 (86-882) 5765857 f (86-882) 5765860 e sign.china@sign.com