



**‘Peel & Stick’**

**Ultimate Tactile**

## INSTALLATION GUIDE

### *Ultimate Tactile with Butyl Adhesive Backing Installation (Overview)*

The use and application of Tactiles (TGSIs) are covered by numerous pieces of legislation, standards and codes. These govern how and where TGSIs are applied and under which circumstances. It is imperative that the person responsible for installing the Ultimate Tactile is familiar with the standards and codes applicable including AS/NZS 1428.4.1:2009.

The Ultimate Tactile has been designed with the final user in mind. Ultimate ‘Peel and Stick’ tactiles can be easily applied to any clean and smooth surface\* and the strong butyl adhesive backing stops the tiles from lifting, be it under the harsh Australian weather or heavy pedestrian foot traffic.

\* We do not recommend installing this product onto asphalt or new concrete surface poured within a 4 week period.

We recommend applying a Surface Primer when installing peel and stick tactiles on to trowled concrete or other porous surfaces. Surface Primer sold separately.

### Installation (Method)

1. Ensure the substrate is free from all debris and is absolutely dry.
2. Measure the area for the tactiles by finding the centre of the pathway first.
3. Layout the tiles to make sure you are putting them in the correct final position.
4. Once happy with the position of the tactiles, mark the substrate with a pencil so you can put the tactile in the exact same location once you have peeled the backing paper off.
3. Peel off paper backing on back of tactile, stick tactiles into previously marked position on substrate.

Note: Butyl adhesive backing is very strong, will stick to clean and flat surface instantly, not allowing much movement after being stuck down.

4. Once you have stuck down all tactiles into position, clear away all rubbish and paper, tactiles are instantly trafficable.



AS/NZS 1428.4.2009

**Peel & Stick**

