









Suitable Surface:

Suitable for both **Indoor** and **Outdoor**, can be installed on:

- Natural Stones
- · Engineered Stones
- Concrete
- Timber Floors
- Rubber Vinyl Flooring
- Ceramic Floors

*Note: NOT Suitable for Asphalt surfaces

Luminance Contrast (LRV)		
	Dry	Wet
Beige	63.4	63.5
Black	3.05	2.76
Blue	8.17	7.36
Grey	43.41	42.56
Red	12.63	12.44
White	86.09	85.6
Yellow	66.51	65.71

PRODUCT INFORMATION & INSTALLATION GUIDE

Tactile Indicator 'Peel & Stick' - TGSI Directional Tile

Specifications		
SKU	TGSIDPS	
Colour Options	Yellow, Black, White, Grey	
Size	300mm x 300mm	
Slip Rating	P5	
Material:	High grade UV stabilised Polyurethane	
Compliance	AS/NZS 1428.4.1:2009	
Warranty	10 Year Limited Warranty	

Description:

The SafetyXpress 'Peel & Stick' Tactiles reduces the installation time of otherwise time consuming installation process.

Made from High grade UV stabilised Polyurethane, these directional bars on top give users a better guide of travel and provide added safety, and warn approaching hazard such as near bus stops or oncoming traffic.

Installation:

Measure the size and area you need to apply these Peel & Stick Tactiles. Work out how many pieces you need exactly first.

Make sure the surface is clean from debris oil or dirt prior to installation. Alternatively you can use acetone to clean and prepare surface first.

Simply **Peel and Stick!**

Note: Tactile Indicators require a 30% luminance contrast with its surrounding substrate to achieve compliance with AS14528.1